

Durez® 33645

Phenolic

Sumitomo Bakelite North America, Inc.

Message:

Durez 33645 is a liquid one-step phenolic resin in Methyl Ethyl Ketone.

Durez 33645 is recommended for use in the manufacture of friction materials.

High heat resistance.

General Information			
Features	High Heat Resistance		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.18	g/cm ³	Internal Method
Thermoset	Nominal Value	Unit	Test Method
Thermoset Mix Viscosity (25°C)	2750	cP	Internal Method
Post Cure Time (160°C)	0.026	hr	
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	75	%	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

