

EVICOM™ EX4/325

Flexible Polyvinyl Chloride

INEOS Compounds

Message:

EVICOM™ EX4/325 is a Flexible Polyvinyl Chloride material. It is available in Europe for extrusion.

Important attributes of EVICOM™ EX4/325 are:

Good Flexibility

High Gloss

Typical application of EVICOM™ EX4/325: Hose/Tubing

General Information			
Features	Good Flexibility High Gloss Low Toxicity		
Uses	Hose Tubing		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.22	g/cm ³	BS 2782 620A
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A, 15 sec)	73		BS 2782 365B
BS Softness	47		BS 2782 365A
Cold Bend	-45	°C	BS 2782 151A
Cold Flexibility	-15	°C	BS 2782 150B
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	19.0	MPa	BS 2782 320A
Tensile Strain (Break)	260	%	BS 2782 320A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT