ALKAMIX™ MB6005

Linear Low Density Polyethylene

Qenos Pty Ltd

Message:

ALKAMIX MB6005 is a combined slip and antiblock masterbatch based on a linear low density polyethylene carrier. It is formulated with slip additive (Erucamide) at a concentration of 8 percent and antiblock additive at a concentration of 25 percent.

ALKAMIX MB6005 can be added to linear low density polyethylene (LLDPE) during extrusion to reduce film blocking and coefficient of friction. The level required will vary according to desired properties and presence of any other additives, however the recommended addition level is between 1 and 2 percent.

The maximum level of addition of MB6005 based on both good manufacturing practice and to ensure conformance to the requirements to the United States Food and Drug Administration Regulations CFR21 is 2.5 percent, when added to a polyethylene formulation free of any other additives.

General Information	
Additive	Antiblock (25%)
	Slip (8%)
Features	Antiblocking
	Slip
Uses	Blending
Forms	Pellets

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

