Fainplast PVC HGK 79

Polyvinyl Chloride

Fainplast Compounds S.r.l

Message:

Fainplast PVC HGK 79 is a Polyvinyl Chloride product. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Wire & Cable. Characteristics include: Chemical Resistant Heat Resistant

General Information			
Features	High Heat Resistance		
	Hydrocarbon Resistant		
	Oil Resistant		
Uses	Cable Jacketing		
	Wire & Cable Applications		
Wire Types	TM3		
	TM53		
Agency Ratings	NF C 32-201-1		
Physical	Nominal Value	Unit	Test Method
Density	1.35 to 1.39	g/cm³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	77 to 81		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	> 19.0	MPa	ISO 527-2
Tensile Strain (Break)	> 300	%	ISO 527-2
Thermal	Nominal Value	Unit	Test Method
Thermal Stability	> 5	hr	CEI 20-34/3-2

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

