

# Lusin® Clean 1020

Thermoplastic

Chem-Trend L.P.

## Message:

Ready-to-use Purging Compound for Screw, Barrel, Nozzle and Hot-runner of Injection Moulding Machines Processing Thermoplastic Elastomers (TPE) and Thermoplastic Polyurethanes (TPU)

### Benefits

Especially dedicated for efficient cleaning of injection moulding machines processing TPE & TPU

No smell during application

Removes residues and encrustations

Suitable for use on hot-runner systems

NSF registered, conforms H2 listing requirements

### Description

Lusin® Clean 1020 is a ready to use purging compound that is specially developed for the processing of TPE and TPU. The purging compound consists of high quality thermoplastic resins as well as highly efficient cleaning additives and does not contain any abrasives. Lusin® Clean 1020 can be used at processing temperatures up to 280°C (536°F). The product is suitable for colour and material change, resulting in parts which immediately have the desired colour.

### Typical Properties

Appearance : Yellowish granules

General Information	
Additive	Unspecified additive
Uses	Cleaning compound
Agency Ratings	NSF Not Rated
Appearance	Yellow
Forms	Particles

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

