

# Sinpolene MBB1263

High Density Polyethylene

Teknor Apex Asia Pacific PTE. LTD.

Message:

SINPOLENE MBB1263 is a high density polyethylene material. This product is available in the Asia-Pacific region and is processed by extrusion. The typical application fields of SINPOLENE MBB1263 are: water pipes/pipes/drinking water

General Information			
Features	General		
Uses	Piping system		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.18	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/10.0 kg)	30 - 50	g/10 min	ASTM D1238
Carbon Black Content	35	%	ASTM D1603
Moisture Content		%	ASTM D3030
Oxidation Induction Time (200°C)	> 60	min	ASTM D3985
Additional Information			

Recommended dosage in HDPE: 7%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

