NEFTEKHIM PP 1548S (H32GA)

Polypropylene Homopolymer

Nizhnekamskneftekhim Inc.

Message:

Product obtained by polymerization of propylene in presence of complex organic metal catalysts.

It incorporates increased long-term thermal stability, thermaloxidative degradation resistance when PP is produced, processed and PP-made articles are exploited, durable antistatic properties, highly effective nucleation, enhanced rigidity of articles, improved rheology of melt.

Application: thin-wall items, containers, flowerpots, dishware.

Technical requirements: TU 2211-136-05766801-2006

General Information					
Additive	Antistatic				
	Nucleating Agent				
Features	Antistatic				
	Controlled Rheology				
	Good Thermal Stability				
	High Rigidity				
	Homopolymer				
	Nucleated				
	Oxidation Resistant				
Uses	Containers				
	Lawn and Garden Equipment				
	Table Products				
	Thick-walled Parts				
Forms	Pellets				
Physical	Nominal Value	Unit	Test Method		
Density	0.900	g/cm³			
Apparent Density	0.48 to 0.52	g/cm³			
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	30 to 40	g/10 min	ASTM D1238		
Ash Content	0.025 to 0.050	%			
Thermal Creep Temperature ¹	90 to 96	°C			
Thermal-oxidative Deterioration (150°C)	15.0	day			
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	82 to 95				
Mechanical	Nominal Value	Unit	Test Method		
Flexural Modulus	1500	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (23°C)	23	J/m	ASTM D256		

Thermal	Nominal Value	Unit	
Vicat Softening Temperature ²	150 to 154	°C	
NOTE			
1.	at load 0.46 H/mm²		
2	in liquid medium under force 10 H		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

