

Hangzhou Jinxin VMCPP Film

PP Film

Hangzhou Jinxin Filming Packaging Co., Ltd.

Message:

Product performance:

Good adhesion, well proportioned,

Heat sealing property

The film with heat sealing property, which can be laminated with BOPP,PET using for convention, it is extensively using for packaging industry.

General Information			
Features	Good Adhesion		
Uses	Laminates		
	Packaging		
Forms	Film		
Mechanical	Nominal Value	Unit	Test Method
Coefficient of Friction	0.62		ASTM D1894
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	25	μm	ASTM D374
Tensile Strength			ASTM D882
MD : Break	54.0	MPa	
TD : Break	33.0	MPa	
Tensile Elongation			ASTM D882
MD : Break	570	%	
TD : Break	610	%	
Seal Strength	0.75	N/mm	
Oxygen Permeability ¹ (23°C)	0.450	cm ³ /m ² /24 hr	ASTM D1434
Water Vapor Transmission	0.50	g/m ² /24 hr	ASTM E96
Optical	Nominal Value	Unit	Test Method
Haze	2.7	%	ASTM D1003
Additional Information	Nominal Value	Unit	Test Method
Wetting Tension	38	dyne/cm	ASTM D2578
NOTE			
1.	0%RH		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

