# Geon<sup>™</sup> Vinyl Flexible A87UF

## Flexible Polyvinyl Chloride

### PolyOne Corporation

#### Message:

Geon<sup>™</sup>Vinyl Flexible A87UF is a flexible polyvinyl chloride product. It can be processed by extrusion or injection molding and is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Geon<sup>™</sup>Vinyl Flexible A87UF applications include hoses and construction applications. Features include: Flame Retardant

UV stability

AdditiveUV sabilizerFaturesUV absorption Flame retardancyFlame retardancyUsesFloor Material Pipe Pipe fittingsAppearanceClear/transparentFormsParticleFornsParticleForessing MethodLittraison Injection moldingPhysicalNominal ValueUnitForger FirstRominal ValuePoper FirstJackSpecific Gravity127Jones ASam A91LittraisonStava A91Shava A91Shava ASalon SittraisonShava ASalon SittraisonSalon SittraisonSalon SittraisonSalon SittraisonSalon SittraisonSalon SittraisonSalon	General Information			
Fame retradencyUsesFloor Material Pipe Pipe fittingsAppearanceClear/transparentFormsOlear/transparentProcessing MethodParticleProcessing MethodExtrusion Injection moldingPhysicalNominal ValueUnitProcessing Method1.27Specific Gravity1.27Specific Gravity1.27Specific Gravity1.27Shaw A91Specific Gravity91Shaw A, 15 seconds82Shaw A, 15 seconds82Shaw A, 15 seconds82TentureASTM D2240Tenture1.86Mominal ValueUnitTenture1.86IndrogendaASTM D638100% strain1.07100% strain3.00100% strain6.11IntracesSolinal ValueUnitTentethodGranspanola9.13IntracesNominal ValueUnitTentethodTensile Elongation <sup>2</sup> (Breag)9.81IntracesNominal ValueUnitTentethodTentalNominal ValueUnitTentethodBatomersNominal ValueIntracesASTM D624Britteness Temperature-21.5"Catomation"ASTM D624Britteness Temperature-21.5"Catomation"ASTM D624Britteness Temperature-21.5"Catomation"ASTM D624Britteness Temperature-21.5<	Additive	UV stabilizer		
Floor Material Pipe Pipe fittingsAppearanceClear/transparentFormsParticleProcessing MethodExtrusion Injection moldingPhysicalNominal ValueUnitPhysicalNominal ValueUnitBardeneerGram'Stat MethodDurometer Hardness127g/cm <sup>3</sup> Shaw A91Test MethodShaw A91Stat Mol Test MethodShaw A91Test MethodShaw A82ASTM D2240Shaw A82Stat Mol Test MethodInsel Stength <sup>1</sup> Test MethodInolicalNominal ValueUnitMechanicalNominal ValueUnitInsel Stength <sup>1</sup> I.7ASTM D2340Shaw A91Stat Mol Test MethodInsel Stength <sup>1</sup> I.7ASTM D2340Shaw A91Stat Mol Test MethodInsel Stength <sup>1</sup> I.7ASTM D2340Insel Stength <sup>1</sup> I.7ASTM D2340Indres1.7MPaInsel Stength <sup>3</sup> 30.0%Insel Stength <sup>3</sup> SallKN/mInsel Stength <sup>3</sup> Sall Sall </td <td>Features</td> <td>UV absorption</td> <td></td> <td></td>	Features	UV absorption		
Pipe Pipe fittingsAppearanceClear/transparentFormsParticleProcessing MethodExtusion Ligction moldingPhysicalNominal ValueUnitPhysicalNominal ValueUnitSpecific Gravity1.27g/cm³Astm D2240UnitTest MethodDurometer HardnessNominal ValueUnitShaw A91ASTM D2240Shaw A, 15 seconds82ASTM D2240Shaw A, 15 seconds82ASTM D2240Fracture18.6MPaASTM D638Tensle Strength <sup>1</sup> 1.7MPaASTM D638Tensle Strength <sup>1</sup> 1.7MPaASTM D638Tensle Elongation <sup>2</sup> (Break)300%ASTM D638Inowisativan11.7MPaASTM D638Tensle Elongation <sup>2</sup> (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTensle Elongation <sup>3</sup> (Break)98.1KI/maASTM D638ElastomersNominal ValueUnitTest MethodTerrature38.1KI/maASTM D638ElastomersNominal ValueUnitTest MethodTerrature2.15°CASTM D746		Flame retardancy		
Pipe Pipe fittingsAppearanceClear/transparentFormsParticleProcessing MethodExtusion Ligction moldingPhysicalNominal ValueUnitPhysicalNominal ValueUnitSpecific Gravity1.27g/cm³Astm D2240UnitTest MethodDurometer HardnessNominal ValueUnitShaw A91ASTM D2240Shaw A, 15 seconds82ASTM D2240Shaw A, 15 seconds82ASTM D2240Fracture18.6MPaASTM D638Tensle Strength <sup>1</sup> 1.7MPaASTM D638Tensle Strength <sup>1</sup> 1.7MPaASTM D638Tensle Elongation <sup>2</sup> (Break)300%ASTM D638Inowisativan11.7MPaASTM D638Tensle Elongation <sup>2</sup> (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTensle Elongation <sup>3</sup> (Break)98.1KI/maASTM D638ElastomersNominal ValueUnitTest MethodTerrature38.1KI/maASTM D638ElastomersNominal ValueUnitTest MethodTerrature2.15°CASTM D746				
Pipe fittingsAppearanceClear/transprentFormsParticleProcessing MethodExtrusionInjection moldingPhysicalNominal ValueMominal ValueUnitSpecific Gravity1.27ArdnessNominal ValueDurometer HardnessJanna ValueShaw A9Shaw A 15 seconds82Shaw A, 15 seconds82Tensile Strength <sup>1</sup> ASTM D2240Tensile Strength <sup>1</sup> Nominal ValueUnitTest MethodTensile Strength <sup>1</sup> ASTM D638Tensile Strength <sup>1</sup> 1.7MPaASTM D638Tensile Strength <sup>1</sup> 1.7Tensile Strength <sup>1</sup> 1.7Tensile Strength <sup>1</sup> 300Sham AASTM D638Tensile Strength <sup>3</sup> 9.8Tensile Strength <sup>3</sup> 9.1Tensile Strength <sup>3</sup> 9.8Tensile Strength <sup>3</sup> 9.8Tensile Strength <sup>3</sup> 9.8Tensile Strength <sup>3</sup> 9.8Tensile Strength <sup>3</sup> 9.1Tensile Strength <sup>3</sup> 9.1Ten	Uses	Floor Material		
AppearanceClear/transparentFormsParticleProcessing MethodExtrusionBrucessing MethodExtrusionSpecific Gravity1.27g/cm³ASTM D792HardnessNominal ValueDurometer HardnessUnitShaw A91Shaw A, 15 seconds82Shaw A, 15 seconds82Facture1.86Inomial ValueUnitTensile Strength <sup>1</sup> Tensile Strength <sup>1</sup> 1.7MPaASTM D638Tensile Strength <sup>1</sup> Shaw A9.11.7MPaASTM D638Tensile Strength <sup>1</sup> Shaw A9.11.7MPaASTM D638Tensile Strength <sup>1</sup> 1.7MPaASTM D638Tensile Elongation <sup>2</sup> (Break)300%ASTM D638ElastomersNominal ValueUnitTensile Strength <sup>3</sup> 9.8.1KurdentStrength <sup>3</sup> 9.8.1KurdentTensile Strength <sup>3</sup> 9.8.1KurdentFacture1075°CASTM D726FarmabilityNominal ValueUnitTensi Etimperature-21.5°CASTM D63FarmabilityNominal ValueUnitTensi Etimperature-21.5°C <td< td=""><td></td><td>Pipe</td><td></td><td></td></td<>		Pipe		
FormsParticleProcessing MethodExtrusion Injection moldingPhysicalNominal ValueUnitSpecific Gravity1.27Morninal ValueUnitMorninal ValueUnitDurometer HardnessNominal ValueShaw A91Shaw A91Shaw A, 15 seconds82Morninal ValueUnitTensile Strength 1Test MethodTensile Strength 1Nominal ValueTensile Strength 1Safa DagaTensile Strength 1MPa10% strain11.710% strain11.7MPaASTM D638ElastomersNominal ValueNominal ValueUnitTensile Ilongation 2 (Break)300%ASTM D638ElastomersNominal ValueNominal ValueUnitTensile Strength 398.1Nominal ValueUnitTensile Strength 3Nominal ValueTensile Strength 398.1KN/mASTM D624ThermalNominal ValueMorninal ValueUnitTest MethodBrittleness Temperature-21.5"CASTM D746		Pipe fittings		
FormsParticleProcessing MethodExtrusion laction moldingPhysicalNominal ValueUnitSpecific Gravity1.27Morninal ValueUnitMorninal ValueUnitDurometer HardnessNominal ValueShaw A91Shaw A91Shaw A, 15 seconds82Morninal ValueUnitMechanicalNominal ValueMorninal ValueUnitTensile Strength 1Staft D638Fracture18.6100% strain11.711.7MPaASTM D638ElastomersNominal ValueNominal ValueUnitTensile Strength 3300%ASTM D638ElastomersNominal ValueNominal ValueUnitTensile Strength 398.1Nominal ValueUnitTensile Strength 398.1Kill Minal ValueUnitTensile Strength 372.6Kill Minal ValueUnitTensile Strength 372.5Kill Minal ValueUnitTensile Strength 4Vorninal ValueStrength 372.5Kill Minal ValueUnitStrength 372.				
Processing MethodExtrusion Injection moldingPhysicalNominal ValueUnitTest MethodSpecific Gravity1.27g/cm³ASTM D792HardnessNominal ValueUnitTest MethodDurometer Hardness91ASTM D2240Shaw A91ASTM D2240Shaw A, 15 seconds82ASTM D2240MechanicalNominal ValueUnitTest MethodTensile Strength <sup>1</sup> STM D638ASTM D638100% strain11.7MPaASTM D638100% strain11.7MPaASTM D638ElastomersNominal ValueUnitTest MethodTensile Elongation <sup>2</sup> (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTear Strength <sup>3</sup> 98.1KN/mASTM D634ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5"CASTM D746	Appearance	Clear/transparent		
Injection moldingPhysicalNominal ValueUnitTest MethodSpecific Gravity1.27g/cm³ASTM D792HardnessNominal ValueUnitTest MethodDurometer Hardness91ASTM D2240Shaw A91ASTM D2240Shaw A, 15 seconds82ASTM D2240MechanicalNominal ValueUnitTest MethodTersile Strength <sup>1</sup> SATM D240ASTM D2240Tersile Strength <sup>1</sup> SATM D638ASTM D638Tensile Elongation <sup>2</sup> (Break)300MPaASTM D638Tensile Elongation <sup>2</sup> (Break)300%1Test MethodTear Strength <sup>3</sup> 98.1KN/mASTM D624TermalNominal ValueUnitTest MethodTermalSecondeCASTM D624TermalSoninal ValueUnitTest MethodTermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746HamabilityNominal ValueUnitTest Method	Forms	Particle		
PhysicalNominal ValueUnitTest MethodSpecific Gravity1.27g/cm³ASTM D792HardnessNominal ValueUnitTest MethodDurometer Hardness91ASTM D2240Shaw A91ASTM D2240Shaw A, 15 seconds82ASTM D2240MechanicalNominal ValueUnitTest MethodTensile Strength <sup>1</sup> STM D638ASTM D638Tensile Strength <sup>1</sup> 11.7MPaASTM D638100% strain11.7MPaASTM D638Tensile Elongation <sup>2</sup> (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTerstrength <sup>3</sup> 98.1kN/mASTM D634ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746	Processing Method	Extrusion		
Specific Gravity1.27g/cm³ASTM D792HardnessNominal ValueUnitTest MethodDurometer Hardness91ASTM D2240Shaw A91ASTM D2240Shaw A, 15 seconds82ASTM D2240MechanicalNominal ValueUnitTest MethodTensile Strength 1Start D2240ASTM D2340Fracture18.6MPaASTM D638100% strain11.7MPaASTM D638ElastomersNominal ValueUnitTest MethodTear Strength 398.1KN/mASTM D634ThermalNominal ValueUnitTest MethodFracture12.5°CASTM D746		Injection molding		
Specific Gravity1.27g/cm³ASTM D792HardnessNominal ValueUnitTest MethodDurometer Hardness91ASTM D2240Shaw A91ASTM D2240Shaw A, 15 seconds82ASTM D2240MechanicalNominal ValueUnitTest MethodTensile Strength 1Start D2240ASTM D2340Fracture18.6MPaASTM D638100% strain11.7MPaASTM D638ElastomersNominal ValueUnitTest MethodTear Strength 398.1KN/mASTM D624ThermalNominal ValueUnitTest MethodFracture21.5°CASTM D746				
HardnessNominal ValueUnitTest MethodDurometer HardnessASTM D2240Shaw A91ASTM D2240Shaw A, 15 seconds82ASTM D2240MechanicalNominal ValueUnitTest MethodTensile Strength 1Staw D240Staw D2240Fracture18.6MPaASTM D638100% strain11.7MPaASTM D638ElastomersNominal ValueUnitTest MethodTensile Elongation 2 (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Physical	Nominal Value	Unit	Test Method
Durometer HardnessASTM D2240Shaw A91ASTM D2240Shaw A, 15 seconds82ASTM D2240MechanicalNominal ValueUnitTest MethodTensile Strength 1Shaw A, 15 SecondsASTM D638Fracture18.6MPaASTM D638100% strain11.7MPaASTM D638Tensile Elongation 2 (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTear Strength 398.1kN/mASTM D624ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Specific Gravity	1.27	g/cm³	ASTM D792
Shaw A91ASTM D2240Shaw A, 15 seconds82ASTM D2240MechanicalNominal ValueUnitTest MethodTensile Strength 1.ASTM D638Fracture18.6MPaASTM D638100% strain11.7MPaASTM D638Tensile Elongation 2 (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTear Strength 398.1kN/mASTM D624ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Hardness	Nominal Value	Unit	Test Method
Shaw A, 15 seconds82ASTM D2240MechanicalNominal ValueUnitTest MethodTensile Strength 1Test MethodASTM D638Fracture18.6MPaASTM D638100% strain11.7MPaASTM D638Tensile Elongation 2 (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTear Strength 398.1kN/mASTM D624ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Durometer Hardness			ASTM D2240
MechanicalNominal ValueUnitTest MethodTensile Strength 1KTM D638Fracture18.6MPaASTM D638100% strain11.7MPaASTM D638Tensile Elongation 2 (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTear Strength 398.1KN/mASTM D624ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Shaw A	91		ASTM D2240
Tensile Strength 1ASTM D638Fracture18.6MPaASTM D638100% strain11.7MPaASTM D638Tensile Elongation 2 (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTear Strength 398.1kN/mASTM D624ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Shaw A, 15 seconds	82		ASTM D2240
Fracture18.6MPaASTM D638100% strain11.7MPaASTM D638Tensile Elongation 2 (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTear Strength 398.1KN/mASTM D624ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Mechanical	Nominal Value	Unit	Test Method
100% strain11.7MPaASTM D638Tensile Elongation 2 (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTear Strength 398.1kN/mASTM D624ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Tensile Strength <sup>1</sup>			ASTM D638
Tensile Elongation 2 (Break)300%ASTM D638ElastomersNominal ValueUnitTest MethodTear Strength 398.1kN/mASTM D624ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Fracture	18.6	MPa	ASTM D638
ElastomersNominal ValueUnitTest MethodTear Strength 398.1kN/mASTM D624ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	100% strain	11.7	MPa	ASTM D638
Tear Strength 398.1kN/mASTM D624ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Tensile Elongation <sup>2</sup> (Break)	300	%	ASTM D638
ThermalNominal ValueUnitTest MethodBrittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Elastomers	Nominal Value	Unit	Test Method
Brittleness Temperature-21.5°CASTM D746FlammabilityNominal ValueUnitTest Method	Tear Strength <sup>3</sup>	98.1	kN/m	ASTM D624
Flammability Nominal Value Unit Test Method	Thermal	Nominal Value	Unit	Test Method
	Brittleness Temperature	-21.5	°C	ASTM D746
Oxygen Index 30 % ASTM D2863	Flammability	Nominal Value	Unit	Test Method
	Oxygen Index	30	%	ASTM D2863

Injection	Nominal Value	Unit
Processing (Melt) Temp	193 - 204	°C
Extrusion	Nominal Value	Unit
Melt Temperature	174 - 179	°C
NOTE		
1.	510 mm/min	
2.	510 mm/min	
3.	C mold, 510mm/min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

