

Kumho PPG 3601

Polyolefin Plastomer

Korea Kumho Petrochemical Co., Ltd.

Message:

PPG 3601 is a copolymer polyol especially designed for the production of flexible slabstock foam. It can be used in blend with conventional polyether polyol for the production of enhanced and high load bearing foam. The foam produced with such blends shows a hardness increase proportional to the level of CPP added.

General Information		
Forms	Liquid	
Physical	Nominal Value	Unit
Acid Number	< 0.10	Mg/g
pH ¹	6.0 to 8.5	
Viscosity (25°C)	0.850 to 1.20	Pa·s
Water Content	< 0.10	%
Hydroxyl Value	39.0 to 44.0	Mg/g
NOTE		
1.	1H2O/10MeOH	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

