

Pemex PX 20020 X

Low Density Polyethylene

Pemex Petroquímica

Message:

Pemex PX 20020 X is a Low Density Polyethylene product. It is available in Latin America or North America.

General Information			
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	10.9	MPa	ASTM D638
Tensile Elongation (Break)	640	%	ASTM D638
Films	Nominal Value	Unit	Test Method
Dart Drop Impact	150	g	ASTM D1709
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	63.7	kN/m	ASTM D1004
Optical	Nominal Value	Unit	Test Method
Clarity	22.0		ASTM D1746
Haze	4.0	%	ASTM D1003

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT