

# UBE Polyethylene F522N

Polyethylene

UBE America, Inc.

## Message:

UBE Polyethylene F522N is a Polyethylene material. It is available in North America. Primary attribute of UBE Polyethylene F522N: Good Processability.  
Typical application of UBE Polyethylene F522N: Packaging

General Information			
Features	Good Moldability		
Uses	Packaging		
	Thin-walled Packaging		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.922	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR)	5.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	52		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	14.0	MPa	ASTM D638
Tensile Elongation (Break)	550	%	ASTM D638
Apparent Bending Modulus	150	MPa	ASTM D747
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-75.0	°C	ASTM D746
Vicat Softening Temperature	90.0	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

