

Sanren M2500CD (Premium-grade)

Polypropylene Homopolymer
SINOPEC Shanghai Petrochemical Co. Ltd.

Message:

The pellet product is colourless and in the shape of a cylinder with satisfied light transmittance and controllable rheological property, good mechanical properties and gamma-ray resistance as well as heat resistance.
Scope of Application: Mainly as special material for medical injection tube with gamma-ray resistance and other similar use.

General Information			
Features	Homopolymer		
	Anti-gamma radiation		
	Controlled rheology		
	Heat resistance, medium		
Uses	Pipe fittings		
	Medical/nursing supplies		
Appearance	Colorless		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	23 - 28	g/10 min	Internal method
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	95		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	> 32.0	MPa	ASTM D638
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact (23°C)	> 22	J/m	Internal method
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	> 151	°C	Internal method
Optical	Nominal Value	Unit	Test Method
Yellowness Index	< 4.0	YI	Internal method
Additional Information			
Cleanliness: 0-5 pieces/kg			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

