

Durez® 11078

Phenolic

SBHPP

Message:

Durez® 11078 is a finely pulverized thermosetting phenolic resin of the one-step type. It is recommended for use in the manufacturing of dry mix for heavy duty linings and truck brake blocks. It will tend to soften at high temperatures and contributes to high friction and fade resistance of the brake.

General Information			
Features	High Friction		
Uses	Lining		
Appearance	Yellow		
Forms	Powder		
Thermal	Nominal Value	Unit	Test Method
Melting Temperature ¹	66.0	°C	Internal method
Additional Information	Nominal Value	Unit	Test Method
Inclined Plate Flow - 0.5 g (125°C)	9.00	cm	Internal method
Screen Mesh - 200 mesh	0.80	%	Internal method
Uncured Properties	Nominal Value	Unit	Test Method
Curing Time (165°C)	0.010	hr	Internal method
NOTE			
1.	Shrink		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

