Solprene® 4302

Styrene Butadiene Styrene Block Copolymer

Dynasol Elastomers

Message:

Solprene 4302 is a linear block copolymer of styrene and butadiene, having 31% of styrene content, most of it forming a polystyrene block, which gives the polymer a thermoplastic behavior.

It has a non-staining antioxidant system; FDA approved, and is essentially gel free with a very clear color.

S-4302 is used as an ingredient for adhesives formulation, as an impact modifier for plastics and as an elastomeric modifier for asphalt mixtures used in paving and roofing.

It is presented as free flowing porous crumb making easy its handling and dissolution.

General Information				
Additive	Antioxidant			
Features	Antioxidant			
	Block Copolymer			
	Food Contact Acceptable			
	High Clarity			
	Linear Polymer Structure			
	Low Gel			
	Porous			
Uses	Adhesives			
	Asphalt Modification			
	Plastics Modification			
Agency Ratings	FDA Food Contact, Unspecified Rating			
Appearance	Clear/Transparent			
Forms	Crumb			
Physical	Nominal Value	Unit	Test Method	
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	6.0	g/10 min	ASTM D1238	
Block Styrene ¹	> 29	%		
Solution Viscosity				
25% in toluene	890	mPa∙s	ASTM D2994	
5.23% in toluene ²	7.0	cSt		
Styrene Content	31	%	ASTM D5775	
Volatile Matter	< 0.75	%	ASTM D5668	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	62		DIN 53505	
Elastomers	Nominal Value	Unit	Test Method	
Tensile Strength	17.0	MPa	ASTM D412	
Tensile Elongation (Break)	1300	%	ASTM D412	
Thermal	Nominal Value	Unit	Test Method	

Glass Transition Temperature	-89.0	°C	ASTM E1356
NOTE			
1.	NM 202-07		
2.	NM 300-11		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

