

# Etinox® EA-4125

Rigid Polyvinyl Chloride

Ercros, S.A.

## Message:

Etinox® EA-4125 is a Rigid Polyvinyl Chloride product. It can be processed by extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Primary characteristic: flame rated.

General Information			
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	1.32	g/cm <sup>3</sup>	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D)	79		ISO 868
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact Strength	69	kJ/m <sup>2</sup>	ISO 180
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	80.0	°C	ISO 306/A
Thermal Stability (180°C)	2	hr	
Flammability	Nominal Value		Test Method
Flame Rating	V-0		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

