

Sumikon® FM-XTK310

Polyphenylene Sulfide
SBHPP

Message:

SUMIKON® FM-XTK-310 is a Heat dissipative thermoplastic molding compounds, Electrical insulative, (10W/mk) Glass fiber and inorganic filler filled Poly phenylene sulfide molding compound.

General Information			
Filler / Reinforcement	Glass fiber reinforced material		
	Inorganic filler		
Features	Insulation		
RoHS Compliance	RoHS compliance		
Appearance	Black		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.85	g/cm ³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	29000	MPa	ASTM D790
Flexural Strength	74.0	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	17	J/m	ASTM D256
Thermal	Nominal Value	Unit	
Thermal Conductivity	10	W/m/K	
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	1.0E+14	ohms·cm	Internal method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT