# Sanren F850EBA (1st-grade)

### Polypropylene Homopolymer

### SINOPEC Shanghai Petrochemical Co. Ltd.

#### Message:

The pellet product is colourless and in the shape of a cylinder with anti-blocking, high anti-static, high light transmittance, good mechanical performance and printability, stress-fracture resistant, excellent chemical stability, as well as fairly good heat-resistance. Scope of Application: Casting film

General Information					
Additive	Anti-caking agent				
	Antistatic property				
Features	High Light Transmission				
	High ESCR (Stress Cracking Resistance)				
	Excellent printability				
	Homopolymer				
	Anti-caking property				
	Antistatic property				
	Heat resistance, medium				
Uses	cast film				
Appearance	Colorless				
Forms	Particle				
Processing Method	Extrusion				
Physical	Nominal Value	Unit	Test Method		
Melt Mass-Flow Rate (MFR) (230°C/2.16					
kg)	5.7 - 11	g/10 min	Internal method		
Ash Content		%			
Fish Eye					
400.0 µm	11.0 - 20.0	pcs/1520 cm <sup>2</sup>			
800.0 µm	1.10 - 3.00	pcs/1520 cm <sup>2</sup>			
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield)	> 25.0	MPa	ASTM D638		
Flexural Modulus	> 790	MPa	Internal method		
Impact	Nominal Value	Unit	Test Method		
Unnotched Izod Impact (23°C)	> 18	J/m	Internal method		
Thermal	Nominal Value	Unit	Test Method		
Vicat Softening Temperature	> 132	°C	Internal method		
Optical	Nominal Value	Unit	Test Method		
Gloss	> 76		Internal method		
Haze	< 2.0	%	Internal method		

Yellowness Index	< 4.0	YI	Internal method
Additional Information	Nominal Value	Unit	

Cleanliness: 6-10 pieces/kg

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

