Trilene® RI10HO

Polypropylene Random Copolymer

Chandra Asri Petrochemical

Message:

RI10HO is a polypropylene ethylene random copolymer with good clarity, for housewares, containers, closures, plastic hanger, and general purpose injection molding applications. Where good impact properties is desired.

This grade uses Unipol® polypropylene technology Union Carbide Corporation with the latest generation of catalyst.

General Information			
Features	General Purpose		
	Good Flexibility		
	Good Impact Resistance		
	Good Strength		
	Medium Clarity		
	Random Copolymer		
Uses	Closures		
	Containers		
	General Purpose		
	Household Goods		
Agency Ratings	FDA 21 CFR 177.1520(c) 3.1a		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.895	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16	10	- (10	
kg)	10	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	81		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	27.0	MPa	ASTM D638
Tensile Elongation (Yield)	15	%	ASTM D638
Flexural Modulus - 1% Secant ²	1000	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	88	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	85.0	°C	ASTM D648
Vicat Softening Temperature	125	°C	ASTM D1525 ³
Peak Melting Temperature ⁴	146	°C	ASTM D3418

Injection	Nominal Value	Unit	
Processing (Melt) Temp	230 to 240	°C	
Mold Temperature	20.0 to 40.0	°C	
NOTE			
1.	50 mm/min		
2.	1.3 mm/min		
3.	Rate B (120°C/h)		
4.	10°C/min, 2nd heat		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

