

Manner Flexible PVC P88023

Flexible Polyvinyl Chloride

Manner Plastics, L.P.

Message:

85°C General Purpose, high shine Profile Extrusion Compound. This product complies with the European Union Restriction on Hazardous Substances (RoHS) directive.

General Information			
Features	General Purpose		
	High Gloss		
Uses	Profiles		
RoHS Compliance	RoHS Compliant		
Processing Method	Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21 to 1.25	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	80		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	17.9	MPa	ASTM D638
Tensile Elongation (Break)	420	%	ASTM D638
Extrusion	Nominal Value	Unit	
Melt Temperature	171	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

