# LNP™ STAT-KON™ DEL13EXC compound

### Polycarbonate

**SABIC Innovative Plastics** 

### Message:

LNP STAT-KON DEL13EXC is a compound based on Polycarbonate resin containing PTFE, Carbon Fiber. Added features of this material include: Easy Molding.

Also known as: LNP\* STAT-KON\* Compound DCL-4013 EM HP

Product reorder name: DEL13EXC

General Information	
UL YellowCard	E207780-101345226
Filler / Reinforcement	Carbon fiber reinforced material
Additive	PTFE lubricant
Features	Good formability
	Lubrication

Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.28	g/cm³	ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	134	MPa	ASTM D638		
Tensile Elongation (Break)	3.0	%	ASTM D638		
Flexural Modulus	9380	MPa	ASTM D790		
Flexural Strength	200	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (23°C)	91	J/m	ASTM D256		
Unnotched Izod Impact (23°C)	480	J/m	ASTM D4812		
Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load (1.8					
MPa, Unannealed, 3.20 mm)	138	°C	ASTM D648		
Electrical	Nominal Value	Unit	Test Method		
Surface Resistivity	10 - 1.0E+4	ohms	ASTM D257		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

