

Chemical Resources PA612157HB

Polyamide 612
Chemical Resources, Inc.

Message:
PA612157HB is a heat stabilized, black nylon 612 polyamide resin suitable for injection molding and extrusion.

General Information			
Additive	Heat Stabilizer		
Features	Heat Stabilized		
Appearance	Black		
Processing Method	Extrusion		
	Injection Molding		

Physical	Nominal Value	Unit	Test Method
Density	1.07	g/cm ³	ISO 1183

Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	64.8	MPa	ISO 527-2
Tensile Strain (Yield)	4.4	%	ISO 527-2
Flexural Modulus	2310	MPa	ISO 178

Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	137	°C	ISO 75-2/B
Melting Temperature	220	°C	ISO 11357-3

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT