

MTEGRITY™ LLDPE LL800G

Linear Low Density Polyethylene

M. Holland Company

Message:

Linear Low Density Polyethylene Powder

Masterbatch Resin

No slip, antiblock or processing aid

Thermal Stabilizer additive

General Information			
Additive	heat stabilizer		
Features	Low density		
	Thermal Stability		
Uses	Composite		
	Masterbatch		
Forms	Powder		
Processing Method	Composite		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.926	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	50	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	15.2	MPa	ASTM D638
Tensile Elongation (Break)	40	%	ASTM D638
Flexural Modulus	448	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT