

Gazprom PSM-115N (Prime Grade)

General Purpose Polystyrene

JSC Gazprom neftekhim Salavat

Message:

APPLICATIONS

For injection molding of industrial products and consumer goods allowed to contact with food.

General Information		
Features	Compliance of Food Exposure	
Uses	Non-specific food applications	
	Industrial application	
	Consumer goods application field	
Forms	Particles	
	Disc	
Processing Method	Injection molding	
Physical	Nominal Value	Unit
Melt Mass-Flow Rate (MFR)	2.0 - 15	g/10 min
Moisture Content		wt%
Particle Size		
2-5 mm Granules	> 98.3	wt%
5-8 mm Granules		wt%
Up to 2.0 mm Granules (Dust)		wt%
Residual monomer-Styrene		wt%
Mechanical	Nominal Value	Unit
Tensile Stress (Break)	> 40.2	MPa
Thermal	Nominal Value	Unit
Vicat Softening Temperature	> 90.0	°C
Additional Information	Nominal Value	Unit

Discs:

Surface: Clean and Shiny

inclusions diameter, within area 10 cm² : 0.2-0.3 mm

inclusions number, within area 10 cm² : <1 pcs

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

