

Daelim Po1y® LL-32HF

Linear Low Density Polyethylene

DAELIM INDUSTRIAL CO., LTD.

Message:

Daelim Po1y®LL-32HF is a linear low density polyethylene product. It is available in the Asia-Pacific region. Daelim Po1y®LL-32HF application areas include film and food contact applications. The main characteristics are: good processing performance.

General Information			
Features	Workability, good		
Uses	Films		
Agency Ratings	ASTM D 1248, I, Class A, Cat. 4		
	FDA 21 CFR 177.1520		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Density	0.917	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.75	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	100	µm	
Tensile Strength			ASTM D882
MD: Yield	13.7	MPa	ASTM D882
TD: Yield	13.2	MPa	ASTM D882
MD: Fracture	52.0	MPa	ASTM D882
TD: Fracture	40.2	MPa	ASTM D882
Tensile Elongation			ASTM D882
MD: Fracture	620	%	ASTM D882
TD: Fracture	650	%	ASTM D882
Dart Drop Impact	660	g	ASTM D1709
Elmendorf Tear Strength			ASTM D1922
MD	120	g	ASTM D1922
TD	120	g	ASTM D1922
Optical	Nominal Value	Unit	Test Method
Haze	15	%	ASTM D1003
Additional Information			
Tear Strength, MD, ASTM D-1004: 140kg/cmTear Strength, TD, ASTM D-1004: 120kg/cm			
Injection	Nominal Value	Unit	
Processing (Melt) Temp	180 - 230	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT