

# HI-ZEX™ 5202B

High Density Polyethylene

Prime Polymer Co., Ltd.

Message:

HI-ZEX™ 5202B is a High Density Polyethylene product. It can be processed by blow molding and is available in Asia Pacific, Europe, or North America. Typical application: Containers. Primary characteristic: impact resistant.

General Information			
Features	Good Impact Resistance		
Uses	Containers		
Processing Method	Blow Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.960	g/cm³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.32	g/10 min	ISO 1133
Environmental Stress-Cracking Resistance	40.0	hr	ASTM D1693
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D, Compression Molded)	64		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus (Compression Molded)	1500	MPa	ISO 527-2
Tensile Stress (Yield, Compression Molded)	31.0	MPa	ISO 527-2
Tensile Strain (Break, Compression Molded)	> 500	%	ISO 527-2
Flexural Modulus (Compression Molded)	1600	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength	No Break		ISO 179
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	128	°C	ISO 306
Melting Temperature	134	°C	ISO 11357-3

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT