

CONAP® AD-6411

Polyurethane

Cytec Industries Inc.

Message:

CONAP AD-6411 is a two-component polyurethane system formulated for filter sealant applications.

General Information		
Uses	Sealants	
Appearance	Amber	
	White	
Physical	Nominal Value	Unit
Specific Gravity		
-- ¹	0.920	g/cm ³
-- ²	1.06	g/cm ³
Hardness	Nominal Value	Unit
Durometer Hardness (Shore D)	45	
Elastomers	Nominal Value	Unit
Tensile Stress		
100% Strain	9.65	MPa
200% Strain	10.9	MPa
Tensile Strength	17.2	MPa
Tensile Elongation (Break)	270	%
Tear Strength	63.9	kN/m
Thermoset	Nominal Value	Unit
Thermoset Components		
Hardener	Mix Ratio by Weight: 89	
Resin	Mix Ratio by Weight: 100	
Thermoset Mix Viscosity (25°C)	16000	cP
NOTE		
1.	Hardener	
2.	Resin	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

