# Royalene® 697

### Ethylene Propylene Diene Terpolymer

#### Lion Copolymer, LLC

#### Message:

A highly extendable ENB polymer with heavy hydrotreated paraffinic oil for TPO/TPV and thermoset applications.

**Unique Features** 

Blends readily in TPO compounds

Reduces mixing time in highly loaded TPO compounds

Highly extendable

Good aging properties

Improved shape retention for hose tube and other extrusions

Very high molecular weight base polymer

High green strength over a broad temperature range

Useful for making low hardness compounds

Extended with a white, hydrotreated paraffinic oil

**Applications** 

TPO and TPV

Automotive applications

Mechanical goods

Hose tubes, Profile extrusions

General Information				
Features	Ultra high molecular weight			
	Oil-filled			
	High strength			
	Hardness, low			
	Medium wide molecular v	veight distribution		
Uses	Thermoforming Application	ons		
	Pipe			
	Pipe fittings			
	Mixing			
	Application in Automobile Field			
	Profile			
Agency Ratings	FDA 21 CFR 177.2600			
	FDA not rated			
Appearance	White-like			
Forms	bag			
Processing Method	Extrusion			
	Profile extrusion molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	0.880	g/cm³	ASTM D792	

Mooney Viscosity <sup>1</sup> (ML 1+4, 125°C)	48	MU	Internal method
Ethylidene Norbornene (ENB) Content	4.5	wt%	Internal method
Oil Type (Paraffinic Oil)	100.0	phr	Internal method
Stabilizer	Non-staining		
Molecular Weight Distribution	Medium		Internal method
Volatile Matter		wt%	Internal method
Additional Information			
E/P weight ratio, internal standard ZS 1	231: 70/30		
NOTE			
1.	Unmilled		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

