BP RPP 2012 T NAT

Polypropylene

Buckeye Polymers, Inc.

Message:

Product Information: Calcium Carbonate Filled PP Grades have a high impact toughness, moderate increased stiffness, and excel in high gloss applications. Our BP RPP C series product line ranges from 10 - 50% in filler levels. These materials can be customized through the addition of UV packages, custom matching, and processing additives.

Features:

Can be UV Stabilized for Increased Resistance Industrial, Outdoor Furniture, and Window Trim

General Information			
Filler / Reinforcement	Calcium Carbonate,20% Filler by Weight		
Features	Good Stiffness		
	Good Toughness		
	High Gloss		
	High Impact Resistance		
Uses	Industrial Applications		
	Outdoor Furnishings		
	Windows & Doors		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	6.0 to 15	g/10 min	ASTM D1238
Ash Content	18 to 23	%	ASTM D5630
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus (23°C)	> 1630	МРа	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	> 53	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

