

# Delta ATL C9-U6

Acetal (POM) Copolymer

Delta Polymers

## Message:

Delta ATL C9-U6 is an Acetal (POM) Copolymer product. It is available in North America.

Characteristics include:

Flame Rated

Impact Modified

General Information			
Additive	Impact Modifier		
Features	Impact Modified		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.33	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR)	3.9	g/10 min	ASTM D1238
Molding Shrinkage - Flow	1.8 to 2.2	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	35.2	MPa	
Break	31.0	MPa	
Tensile Elongation (Break)	67	%	ASTM D638
Flexural Modulus	1450	MPa	ASTM D790
Flexural Strength (Yield)	46.9	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	130	J/m	ASTM D256
Thermal	Nominal Value	Unit	
Melting Temperature	160	°C	
Flammability	Nominal Value		Test Method
Flame Rating	HB		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT