Ad-Tech Epoxy EL-335

Epoxy; Epoxide

Ad-Tech Plastic Systems Corp.

Message:

Ad-Tech Epoxy EL-335 is an Epoxy; Epoxide (Epoxy) product. It can be processed by laminating and is available in North America. Typical application: Coating Applications.

Characteristics include:

High Hardness

Impact Resistant

Low Viscosity

General Information				
Features	Good Impact Resistance			
	High Hardness			
	Low Viscosity			
	Non-MDA Cured			
Uses	Laminates			
Appearance	Amber			
Forms	Pellets			
Processing Method	Laminating			
Physical	Nominal Value	Unit	Test Method	
Apparent Density	1.14	g/cm³	ASTM D1895	
Molding Shrinkage - Flow	0.10	%	ASTM D955	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore D)	85		ASTM D2240	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Modulus	9860	MPa	ASTM D638	
Tensile Strength (Yield)	241	MPa	ASTM D638	
Tensile Elongation (Yield)	2.7	%	ASTM D638	
Flexural Modulus	14000	MPa	ASTM D790	
Flexural Strength (Yield)	338	МРа	ASTM D790	
Compressive Strength	103	MPa	ASTM D695	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (1.8				
MPa, Unannealed)	86.7	°C	ASTM D648	
Glass Transition Temperature	119	°C	ASTM E1356	
CLTE - Flow	6.1E-5	cm/cm/°C	ASTM D696	
Thermoset	Nominal Value	Unit	Test Method	
Thermoset Components				

Mix Ratio by Volume: 1.0

Hardener	Mix Ratio by Weight: 20
	Mix Ratio by Weight: 100

Resin	Mix Ratio by Volume: 4.	Mix Ratio by Volume: 4.1		
Pot Life (25°C)	40 to 50	min		
Shelf Life	52	wk		
Thermoset Mix Viscosity (25°C)	1130	сР	ASTM D2393	
Demold Time (25°C)	4300	min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

