Huafon JF-S-AH7025

Polyurethane

Huafon Group Co., Ltd.

Message:

Non-Yellowing Type

Characteristics

Non-yellowing type, cold resistance, hydrolysis resistance, NOx resistance, excellent solvent resistance, swelling resistance.

Applications

Micro fibre, Garments, Shoes, Sofa

| General Information | | | |
|-------------------------------|---------------------------|------|--|
| Features | Hydrolysis Resistant | | |
| | Low Temperature Resistant | | |
| | Solvent Resistant | | |
| | | | |
| Uses | Footwear | | |
| | Furniture | | |
| | Textile Applications | | |
| | | | |
| Additional Information | Nominal Value | Unit | |
| Solvents | DMF/TOL/IPA | | |
| Uncured Properties | Nominal Value | Unit | |
| Solids Content | 24 to 26 | % | |
| Viscosity (25°C) | 60 to 120 | Pa·s | |
| Cured Properties | Nominal Value | Unit | |
| Tensile Modulus (100% Secant) | 1.50 to 2.50 | MPa | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

MPa

%

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

> 35.0

> 600

Tel: +86 21 5895 8519

Tensile Strength

Tensile Elongation at Break

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

