KumhoSunny PC/ABS HAC8260H

Polycarbonate + ABS

Shanghai KumhoSunny Plastics Co., Ltd.

Message:

HAC8260H is high flow PC/ABS resin. HAC8260H has an excellent low temperature resistance properties. HAC8260H is mainly used in mobile phone housing, etc.

General Information				
Features	High Flow			
	Low Temperature Resistant			
Uses	Cell Phones			
	Housings			
UL File Number	E254819			
	E65424			
Forms	Pellets			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.12	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (230°C/10.0				
kg)	25	g/10 min	ASTM D1238	
Molding Shrinkage - Flow	0.50 to 0.70	%	ASTM D955	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	56.0	MPa	ASTM D638	
Tensile Elongation (Break)	100	%	ASTM D638	
Flexural Modulus	2100	MPa	ASTM D790	
Flexural Strength	80.0	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (3.20 mm)	750	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (1.8				
MPa, Unannealed)	106	°C	ASTM D648	
Vicat Softening Temperature	118	°C	ASTM D1525 ¹	
Electrical	Nominal Value	Unit	Test Method	
Surface Resistivity	> 1.0E+15	ohms	IEC 60093	
Volume Resistivity	> 1.0E+15	ohms•cm	IEC 60093	
Flammability	Nominal Value	Unit	Test Method	
Flame Rating (1.60 mm)	НВ		UL 94	
Additional Information	Nominal Value			

CSA File No.	LS 66457		
Injection	Nominal Value	Unit	
Drying Temperature	100 to 110	°C	
Drying Time	4.0 to 6.0	hr	
Processing (Melt) Temp	240 to 280	°C	
Mold Temperature	60.0 to 90.0	°C	
NOTE			
1.	Rate B (120°C/h)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

