

APEX® 91-A1386C-63NT

Flexible Polyvinyl Chloride

Teknor Apex Company

Message:

APEX® 91-A1386C-63NT is a Flexible Polyvinyl Chloride material. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Primary attribute of APEX® 91-A1386C-63NT: RoHS Compliant.
Typical application of APEX® 91-A1386C-63NT: Medical/Healthcare

| General Information | | | |
|--------------------------------------|---------------------------------|-------|-------------|
| Uses | Medical/Healthcare Applications | | |
| RoHS Compliance | RoHS Compliant | | |
| Appearance | Clear/Transparent | | |
| Forms | Pellets | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 1.22 | g/cm³ | ASTM D792 |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore A, 15 sec) | 63 | | ASTM D2240 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Strength (Break) | 12.5 | MPa | ASTM D638 |
| Tensile Elongation (Break) | 370 | % | ASTM D638 |
| Thermal | Nominal Value | Unit | Test Method |
| Continuous Use Temperature | 105 | °C | ASTM D794 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

