Zhongfa PP ZF-UV2

Polypropylene

Yuyao Zhongfa Engineering Plastics Co. Ltd.

Message:

Zhongfa PP ZF-UV2 is a polypropylene material. This product is available in the Asia-Pacific region and is processed by injection molding. The main features of Zhongfa PP ZF-UV2 are:

high gloss

Good UV resistance

chemical resistance

UV stability

The typical application field of Zhongfa PP ZF-UV2 is: automotive industry

General Information					
Additive	UV stabilizer				
Features	Highlight				
	Good UV resistance				
	Good liquidity				
	Good chemical resistance				
Uses	Application in Automobil	Application in Automobile Field			
Forms	Particle				
Processing Method	Injection molding	Injection molding			
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	0.910	g/cm³	ASTM D792		
Melt Mass-Flow Rate (MFR)	3.0	g/10 min	ASTM D1238		
Molding Shrinkage - Flow	1.8	%	ASTM D955		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	66		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength	35.0	MPa	ASTM D638		
Tensile Elongation (Break)	100	%	ASTM D638		
Flexural Modulus	1600	MPa	ASTM D790		
Flexural Strength	38.0	МРа	ASTM D790		
Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load (0 MPa, Unannealed)	45 120	۴С	ASTM D648		
Additional Information					
Aging Resistance at 150°C: >1000 hrNo	otched Izod Impact, ASTM D256: 4	kJ/m ² Unnotched Izod Impact, ASTM	D256: No Break		
Injection	Nominal Value	Unit			
Drying Temperature	90.0 - 95.0	°C			
Drying Time	2.0 - 3.0	hr			
Processing (Melt) Temp	195 - 225	°C			

Mold Temperature	45.0 - 80.0	°C	
Injection Pressure	60.0 - 90.0	MPa	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

