

APEX® 84129

Flexible Polyvinyl Chloride

Teknor Apex Company

Message:

APEX® 84129 is a Flexible Polyvinyl Chloride material. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Primary attribute of APEX® 84129: RoHS Compliant.
Typical application of APEX® 84129: Wire & Cable

General Information			
Uses	Wire & Cable Applications		
RoHS Compliance	RoHS Compliant		
Appearance	Opaque		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.38	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore C, 10 sec)	70		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	22.4	MPa	ASTM D638
Tensile Elongation (Break)	270	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	80.0	°C	ASTM D794
Brittleness Temperature	-21.0	°C	ASTM D746
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity (50°C)	8.4E+13	ohms · cm	ASTM D257
Dielectric Constant			ASTM D150
1 kHz	4.47		
1 MHz	3.20		
Dissipation Factor			ASTM D150
1 kHz	0.076		
1 MHz	0.060		
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	30	%	ASTM D2863

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

