NuSil MED-4244

Silicone

NuSil Technology

Message:

NuSil Technology's unrestricted materials may be considered for long-term implant applications (greater than 29 days).

Low consistency elastomers (LCEs) are useful alternatives to liquid silicone rubber (LSR) and high consistency rubber (HCR) for end users who need a low viscosity elastomer which provides other unique properties.

LCEs lend themselves to applications that require a pourable, self-leveling silicone. Applications include: encapsulating a device, backfi lling a void, potting an electronic component that cannot withstand exposure to high heat, or prototyping a mold.

Comments: FLOWABLE, MEDIUM DUROMETER

General Information			
Features	Good Flow		
	Good Processability		
	Low Viscosity		
	Medium Hardness		
Uses	Electrical/Electronic Applications		
	Medical/Healthcare Applications		
	USD CL VII		
Agency Ratings	USP Class VI		
Appearance	Clear/Transparent		
Processing Method	Encapsulating		
	Potting		
Mechanical	Nominal Value	Unit	
Tensile Strength (200% Strain)	3.31	MPa	
Thermoset	Nominal Value	Unit	
Thermoset Components			
Part A	Mix Ratio by Weight: 10		
Part B	Mix Ratio by Weight: 1.0		
Post Cure Time (150°C)	1.0	hr	
Additional Information	Nominal Value	Unit	
Cure System	Platinum		
Uncured Properties	Nominal Value	Unit	
Density	1.10	g/cm³	
Viscosity			
1	0.27	Pa·s	
2	120	Pa·s	
Curing Time (177°C)	0.083	hr	
Pot Life (25°C)	240	min	
Cured Properties	Nominal Value	Unit	

Shore Hardness (Shore A)	40		
Tensile Strength	5.86	MPa	
Tensile Elongation at Break	300	%	
Tear Strength	26.3	kN/m	
NOTE			
1.	Part B		
2.	Part A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

