

Guang Sung PVC GPMD70

Rigid Polyvinyl Chloride

Guang Sung Plastics (GSPL)

Message:

Guang Sung PVC GPMD70 is a Rigid Polyvinyl Chloride product. It can be processed by coextrusion or injection molding and is available in Asia Pacific. Typical application: Coating Applications. Primary characteristic: rohs compliant.

General Information	
Uses	Coating Applications
RoHS Compliance	RoHS Compliant
Forms	Pellets
Processing Method	Coextrusion Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.36	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	70		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	45.1	MPa	ASTM D638
Tensile Elongation (Break)	> 100	%	ASTM D638
Flexural Modulus	2350	MPa	ASTM D790
Flexural Strength	67.7	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	410	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

