

Sinpolene MBW0651/A

Linear Low Density Polyethylene
Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinpolene MBW0651/A is a polyethylene-based white masterbatch designed specifically for use in tubular film blowing, blow moulding and extrusion of polyolefins. With its high pigment loading, Sinpolene MBW0651/A offers high colouring value with excellent quality and performance. Sinpolene MBW0651/A is delivered as free flowing pellets for processing convenience.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High opacifying power
- * Excellent whiteness

General Information	
Filler / Reinforcement	Titanium Dioxide Equivalent, 65% filler by weight
Features	General
Uses	Packaging
RoHS Compliance	RoHS compliance
Appearance	White
Forms	Particle
Processing Method	Film extrusion
	Sheet extrusion molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.09	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	5.0 - 30	g/10 min	ASTM D1238
Moisture Content		%	ASTM D3030

Additional Information
Recommended dosage: 2 - 5%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT