

ASACLEAN™ NewE

Proprietary
ASACLEAN - Sun Plastech Inc.

Message:

PURGE COMPOUND FOR SCREW AND BARREL
Special to change to transparent materials
Temperature range : 160°C - 270°C
ASACLEAN ® NewE is particularly efficient to change to transparent materials and is also recommended for low temperature applications. The fields of appliance are
Injection Moulding
Extrusion
It is characterized by the well known ASACLEAN ® purging power and efficiency. ASACLEAN ® NewE is neither abrasive nor corrosive and is applicable for
Colour Changes
Material Changes to standard polymers
"Sealing"
Hot Runner Cleaning
Contact:
VELOX GmbH
Tel: +49 - (0)40 - 369 688 - 0
eMail: info@velox.com
Website: <http://www.velox.com>

General Information	
Features	Non-Corrosive
Uses	Purging Compound
Forms	Pellets
Processing Method	Extrusion
	Injection Molding

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT