

# Sylvin 86012-66 Clear

Polyvinyl Chloride  
Sylvin Technologies Incorporated

Message:  
Sylvin 86012-66 Clear Is A Vinyl Compound Formulated For Profile Extrusion Applications. This Compound Meets The Requirements Of UL 94 HB Flammability But Is Not Listed.

General Information			
Uses	Profiles		
Appearance	Clear/Transparent		
Processing Method	Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.19	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	66		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	12.1	MPa	ASTM D638
Tensile Elongation (Break)	400	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	43.8	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	157 to 168	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT