

Lusin® Protect O 45 F

Unspecified

Chem-Trend L.P.

Message:

Grease-based Anticorrosion and Lubricating agent

Benefits

NSF registered, conforms to H1 listing requirements

Stable, transparent protective film

Repels water

Description

Lusin® Protect O 45 F is an efficient anticorrosion agent that also shows lubricating properties. The grease base of Lusin® Protect O 45 F enables the product to penetrate into very fine cracks.

Lusin® Protect O 45 F conforms to H1 category code and therefore complies with FDA 21 CFR §178.3570.

Typical Properties

Appearance : Transparent liquid

Corrosion protection per DIN 50017 on steel type RST-37-2 : No corrosion after 40 hours

Salt water spray test per DIN 50021 on steel type 101-A : No corrosion after 50 hours

Application

Lusin® Protect O 45 F s mainly used to protect moulds and dies dedicated for processing thermoplastic resins against corrosion.

General Information		
Agency Ratings	FDA 21 CFR 178.3570	
	NSF Not Rated	
Appearance	Clear/transparent	
Forms	Liquid	
Thermal	Nominal Value	Unit
Service Temperature		°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

