LightSpan® LS-3354

Silicone

NuSil Technology

Message:

From LEDs to fiber optics, NuSil Technology's LightSpan[™] brand product line delivers the most comprehensive line of refractive index matching adhesives, encapsulants and thermosets available. The benefits of silicone include the following: Thermal Stability Low Ionic Species Maintain Optical Clarity (90% minimum @ 400nm) Low Moisture Absorption (<0.4%) Optimization for UV Resistance Adjustable Cure Low Outgassing Low Shrinkage, <1% Low Modulus: Stress reduction for bonding materials with different coefficients of thermal expansion Gernal Purpose: Optical Gels Comments: Use with Phosphor

General Information		
Features	Good Thermal Stability	
	Good UV Resistance	
	Low Moisture Absorption	
	Low Shrinkage	
	Low to No Outgassing	
Forms	Gel	
Optical	Nominal Value	
Refractive Index	1.540	
Thermoset	Nominal Value	Unit
Thermoset Components		
Part A	Mix Ratio by Weight: 1.0	
Part B	Mix Ratio by Weight: 1.0	
Uncured Properties	Nominal Value	Unit
Viscosity	5.4	Pa·s
Curing Time (70°C)	1.0	hr
Pot Life	90	min
Cured Properties	Nominal Value	Unit
Shore Hardness		
Shore OOO	65	
Shore OO	65	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

