# POLYPRO® SB9108H

### Polypropylene Copolymer

YUHWA Korea Petrochemical Ind. Co., Ltd.

#### Message:

POLYPRO® SB9108H is a Polypropylene Copolymer (PP Copolymer) material. It is available in Asia Pacific for injection molding. Important attributes of POLYPRO® SB9108H are:

Flame Rated

**RoHS Compliant** 

Copolymer

High Gloss

High Stiffness

Typical applications include:

Automotive

Electrical/Electronic Applications

**Food Contact Applications** 

General Information				
Features	Block Copolymer			
	Good Impact Resistance			
	High Gloss			
	High Stiffness			
Uses	Automotive Applications			
	Electrical/Electronic Applications			
Agency Ratings	FDA Food Contact, Unspecified Rating			
RoHS Compliance	RoHS Compliant			
Forms	Pellets			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Density	0.910	g/cm³	ASTM D1505	
Melt Mass-Flow Rate (MFR) (230°C/2 kg)	16 10	g/10 min	ASTM D1238	
Molding Shrinkage - Flow	1.4 to 1.8	%	Internal Method	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	97		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	29.4	MPa	ASTM D638	
Tensile Elongation (Break)	> 200	%	ASTM D638	
Flexural Modulus	1470	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact			ASTM D256	
-20°C	29	J/m		
25°C	98	J/m		

Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load (1.8					
MPa, Unannealed)	130	°C	ASTM D648		
Vicat Softening Temperature	152	°C	ASTM D1525		
Peak Melting Temperature	168	°C	ASTM D3418		
RTI Elec	125	°C	UL 746		
Flammability	Nominal Value		Test Method		
Flame Rating (All Colors)	НВ		UL 94		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

