

RELENE® 22FA002

Low Density Polyethylene
Reliance Industries Limited

Message:

22FA002 is a film grade Low Density Polyethylene (LDPE) produced by high pressure tubular process. It has been specially designed for the production of film with good environmental stress crack resistance, mechanical and impact resistance. Film produced from this grade is ideally suitable for heavy duty applications.

General Information			
Features	Food Contact Acceptable		
	Good Impact Resistance		
	High ESCR (Stress Crack Resist.)		
Uses	Film		
	Heavy-duty Bags		
	Liners		
	Shrink Wrap		
Agency Ratings	FDA 21 CFR 177.1520		
	IS 10141-1982		
	IS 10146-1982		
Processing Method	Film Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.20	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D882
MD : Break, 40 µm,Blown Film	26.0	MPa	
TD : Break, 40 µm,Blown Film	24.0	MPa	
Tensile Elongation			ASTM D882
MD : Break, 40 µm,Blown Film	400	%	
TD : Break, 40 µm,Blown Film	600	%	
Dart Drop Impact (40 µm, Blown Film)	220	g	ASTM D1709A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

