

CEPLA CT-251

Polypropylene

CEPLA Co., LTD

Message:

CEPLA CT-251 is a Polypropylene material filled with filler. It is available in Asia Pacific, Europe, or Latin America.

Important attributes of CEPLA CT-251 are:

High Stiffness

Scratch Resistant

Typical application of CEPLA CT-251: Automotive

General Information	
Filler / Reinforcement	Filler
Features	High Stiffness
	Scratch Resistant
Uses	Automotive Applications
	Automotive Interior Parts

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.980	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	8.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	100		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	34.3	MPa	ASTM D638
Flexural Modulus	2940	MPa	ASTM D790
Flexural Strength	35.3	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact (23°C)	25	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature	135	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT