

# GAPEKK™ 3100PF

Polyetherketoneketone

Gharda Chemicals Ltd.

## Message:

Product Details: Ultra High performance thermoplastic polymer, unfilled Polyether Ketone Ketone (PEKK), semi crystalline, powder for compression molding, standard flow, suitable for food contact applications, color natural white.

General Information			
Features	Food Contact Acceptable		
	Good Flow		
	Semi Crystalline		
Appearance	White		
Forms	Powder		
Processing Method	Compression Molding		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.15	g/cm <sup>3</sup>	ASTM D1895B
Particle Size Distribution - D(100)	< 200.0	µm	
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	300	°C	UL 746B
Glass Transition Temperature	176	°C	ASTM D3418
Melting Temperature	396	°C	ASTM D3418
Flammability	Nominal Value	Test Method	
Flame Rating (0.800 mm)	V-0	UL 94	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT