

# Silmar® SIL93AE-1958AL

Thermoset Polyester

Interplastic Corporation

## Message:

These high-performance resins are mixed with granite effect fillers and spray-applied to form decorative coatings on sinks, countertops and wall panels. They resist draining when applied to vertical surfaces.

Silmar granite effect resins are formulated with isophthalic, NPG polymers and acrylic modified (MMA) to withstand water and higher heat, resist scratches and protect against fading and discoloration caused by UV light. These resins produce a solid void-free surface that is resistant to staining.

General Information		
Features	Good UV Resistance	
	High Scratch Resistance	
	Isophthalic	
Uses	Coating Applications	
	Decorative Parts	
Additional Information	Nominal Value	Unit
Gel to Peak	7.00 to 11.0	
Uncured Properties	Nominal Value	Unit
Viscosity		
Brookfield HBT <sup>1</sup>	2.8 to 4.2	Pa · s
Brookfield HBT <sup>2</sup>	18 to 28	Pa · s
Gel Time	7.0 to 11	min
NOTE		
1.	RV # 4 at 20 RPM	
2.	RV #4 at 2 RPM	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT