

LCA® M-90 Type

Acetal (POM) Copolymer

UniPlas, Inc.

Message:

LCA® M-90 Type is an Acetal (POM) Copolymer material. It is available in North America for injection molding. Primary attribute of LCA® M-90 Type: Copolymer.

General Information			
Features	Copolymer		
	General Purpose		
Uses	General Purpose		
Appearance	Black		
	Natural Color		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.40	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	9.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	65.5	MPa	
Break	62.7	MPa	
Tensile Elongation (Break)	30	%	ASTM D638
Flexural Modulus	3030	MPa	ASTM D790
Flexural Strength (Yield)	93.1	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	53	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	167	°C	ASTM D789

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

