

TAISOX 7200F

High Density Polyethylene
Formosa Plastics Corporation

Message:

TAISOX 7200F is a high density polyethylene material. This product is available in North America, Europe or Asia Pacific region. The processing method is injection molding. The main characteristics of TAISOX 7200F are: rapid prototyping cycle.

Typical application areas include:

- container
- textile/fiber
- home apps
- bottle

General Information			
Features	High density		
	Fast molding cycle		
	Good liquidity		
Uses	Thin wall container		
	Household goods		
	Bottle		
	Food container		
	Fiber		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density	0.955	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	22	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	67		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	27.9	MPa	ASTM D638
Fracture	14.7	MPa	ASTM D638
Tensile Elongation (Break)	700	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Tensile Impact Strength	93.2	kJ/m ²	ASTM D1822
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-70.0	°C	ASTM D746
Vicat Softening Temperature	125	°C	ASTM D1525
Melting Temperature	133	°C	

Additional Information

Notched Izod Impact Strength, ASTM D256: 3.5 kg-cm/cm²

Injection	Nominal Value	Unit
Processing (Melt) Temp	250 - 270	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

